

BV/2 EM 8-0+05 AG 2.0mm

Product Datasheet

Product information

Article number	01010006
Standard width	3000 mm
Maximum width	

Construction

Top face material	PVC
Surface structure	Glossy
Coating thickness	0.5 mm
Colour	a. green
Bottom cover face	
Surface structure	Fabric
Colour	white
Tension member material	Polyester fabric
Number of fabric plies	2

Technical data

Total thickness	2.0
Weight	2.5 kg/m ²
Force elongation at 1%	8 N/mm
Min. Pulley Ø	30 mm
Friction coefficient of bottom face against steel panel according ISO 21182	0.25
Permissible operating temperature	-10°C/+80°C
Hardness of top face coating as per DIN 53505 (Shore A)	80 ShA
Electrostatic	

Properties

Lateral stiffness	√
Troughable	
Suitable for curves	
Food grade (FG)	
Anti-microbial (AM)	
Heat resistant (HR)	
Fray-less (FL)	
Flame-retardant (FR)	
Energy saving (ES)	
Noise development	Regular
Belt support	Support slider bed

Joining Technical Info

Joint type	Finger over Finger
Upper platen Temp.	175 °C
Lower platen Temp.	170 °C
Curing time	4 min
Pressure	2 Bar