

BV/3 EF 15-S18+07 AG 4.0mm

Product Datasheet

Product information

| | |
|----------------|---------|
| Article number | A203 |
| Standard width | 3000 mm |
| Maximum width | |

Construction

| | |
|-------------------------|------------------|
| Top face material | PVC |
| Surface structure | Glossy |
| Coating thickness | 0.7 mm |
| Colour | a. green |
| Bottom cover face | |
| Surface structure | PVC |
| Colour | a.green |
| Tension member material | Polyester fabric |
| Number of fabric plies | 3 |

Technical data

| | |
|---|-----------------------|
| Total thickness | 4.0 |
| Weight | 4.5 kg/m ² |
| Force elongation at 1% | 15 N/mm |
| Min. Pulley Ø | 80 mm |
| Friction coefficient of bottom face against steel panel according ISO 21182 | 0.25 |
| Permissible operating temperature | -10°C/+80°C |
| Hardness of top face coating as per DIN 53505 (Shore A) | 80 ShA |
| Electrostatic | |

Properties

| | |
|----------------------|-----------------|
| Lateral stiffness | |
| Troughable | √ |
| Suitable for curves | √ |
| Food grade (FG) | |
| Anti-microbial (AM) | |
| Heat resistant (HR) | |
| Fray-less (FL) | |
| Flame-retardant (FR) | |
| Energy saving (ES) | |
| Noise development | Regular |
| Belt support | Support rollers |

Joining Technical Info

| | |
|--------------------|--------------------|
| Joint type | Finger over Finger |
| Upper platen Temp. | 180 °C |
| Lower platen Temp. | 175 °C |
| Curing time | 4 min |
| Pressure | 2 Bar |